

[Web](#) [Images](#) [Video](#) [Maps](#) [News](#) [Shopping](#) [Gmail](#) [more](#)
[Sign in](#)

bytes count as identifier in tunneling

Search

[Advanced Search](#)  
[Preferences](#)
[Web](#) [Show options...](#)Results 1 - 10 of about **35,000** for **bytes count as identifier in tunneling**. (0.25 seconds)

### Tunnel configuration - Patent

Column 473 "RECEIVED PACKET **BYTE COUNT**" indicates the numbers of packets and ... and/or **bytes** dropped, security information, client **identifiers**, **tunnel** ...  
[www.faqs.org/patents/app/20030016337](http://www.faqs.org/patents/app/20030016337) - [Cached](#) - [Similar pages](#)

### 2.2.1.3.1 ipsecNFA{GUID} Object Description

Auth-Method-**Count** (4 **bytes**): This **MUST** be the number of Auth-Method binary ... IPv6-**Tunnel-Mode-ID** (16 **bytes**): The **identifier** that specifies this NFA ...  
[msdn.microsoft.com/en-us/library/cc232439\(PROT.13\).aspx](http://msdn.microsoft.com/en-us/library/cc232439(PROT.13).aspx) - [Cached](#) - [Similar pages](#)

### Layer 2 Tunnel Protocol - Cisco Systems

**id** —Local **tunnel ID**. local-name—Name of local end of **tunnel**. remote-name—Name of remote end of **tunnel**. packets. Packet/**byte count**. ...  
[www.cisco.com/en/US/docs/ios/12\\_0t/12\\_0t1/feature/guide/12tpT.html](http://www.cisco.com/en/US/docs/ios/12_0t/12_0t1/feature/guide/12tpT.html) - [Cached](#) - [Similar pages](#)

### Configure Logical Interface Properties

oam-liveness { up-**count** cells ; down-**count** cells ; } oam-period (disable | seconds) ; ... dcli dcli-**identifier**. Point-to-point interfaces with Frame Relay encapsulation. ... fragment-threshold **bytes**. Multilink interfaces. ... Configure a Unicast **Tunnel** and Configure a VT Interface for Route Table Lookup. ...  
[www.juniper.net/techpubs/software/junos/junos56/swoonfig56-interfaces/html/interfaces-logical-config.html](http://www.juniper.net/techpubs/software/junos/junos56/swoonfig56-interfaces/html/interfaces-logical-config.html) - [Cached](#) - [Similar pages](#)

### Header compression for general packet radio service tunneling ...

Once can map each RTP context to a GTP TID (GTP **tunnel ID**) (the maximum number ... clock at the decompressor (or receiving RTP peer) is used to **count** the cycles. ... 1 **byte**), a two **byte** length field, a two to four **byte tunnel identifier** ...  
[www.patentstorm.us/patents/6839339/description.html](http://www.patentstorm.us/patents/6839339/description.html) - [Similar pages](#)

### fxr.watson.org: NETBSD20 sys/netinet/ip\_mroute.h

Jun 26, 2003 ... source navigation ] [ diff markup ] [ **identifier** search ] [ freetext search ... cached route if this is a **tunnel** \*/ 142 struct callout v\_repq\_ch; ... pkt **count** for src-grp \*/ 162 u\_long mfc\_byte\_cnt; /\* **byte count** for ...  
[fxr.watson.org/fxr/source/inetinet/ip\\_mroute.h?v=NETBSD20](http://fxr.watson.org/fxr/source/inetinet/ip_mroute.h?v=NETBSD20) - [Cached](#) - [Similar pages](#)

### TunnelServlet xref

42 \* 43 \* \$Id: TunnelServlet.java,v 1.3 2007/03/10 12:42:13 tanderson Exp \$ 44 ... setIdlePeriod(idlePeriod); 136 137 log("OpenJMS **tunnel** accepting requests .... 279 **byte**] data = new **byte**[1024]; 280 int **count** = 0; 281 while (**count** ! ...  
[openjms.sourceforge.net/modules/openjms-tunnel/xref/org/exolab/jms/net/tunnel/TunnelServlet.html](http://openjms.sourceforge.net/modules/openjms-tunnel/xref/org/exolab/jms/net/tunnel/TunnelServlet.html) - [Similar pages](#)

### (PPT) Control Update

File Format: Microsoft Powerpoint - [View as HTML](#)  
 uchar type; // 0 = Normal, 1 = substrate only (i.e. **tunnel**) ... qmID\_t: unsigned **Byte**; 2-bit **QM identifier**; schID\_t: unsigned **Byte**; 3-bit qm relative ...  
[www.aif.wustl.edu/projects/techX/ppt/Types.ppt](http://www.aif.wustl.edu/projects/techX/ppt/Types.ppt) - [Similar pages](#)

### Header compression for general packet radio service **tunneling** ...

Jan 21, 2004 ... (It should be noted that the TID (**tunnel ID**) value is based upon the release 97 version ..... then the CSRC list and CC **count** will also change. .... a two to four **byte tunnel identifier** (TID) field, a two **byte** sequence ...  
[www.freepatentsonline.com/EP1122925.html](http://www.freepatentsonline.com/EP1122925.html) - [Similar pages](#)  
by M Choo Chuah - 2004 - [Related articles](#)

### Network Working Group N. Brownlee Request for Comments: 2924 The ...

AVP Length A 16-bit field contains the total object length in **bytes**. .... 50 Acct-Multi-Session-Id 51 Acct-Link-Count These **identifiers** were designed to ...  
[www.ietf.org/rfc/rfc2924.txt](http://www.ietf.org/rfc/rfc2924.txt) - [Cached](#) - [Similar pages](#)  
by A Attributes - [Related articles](#)

[1](#) [2](#) [3](#) [4](#) [5](#) [6](#) [7](#) [8](#) [9](#) [10](#) [Next](#)

---

[Search within results](#) - [Language Tools](#) - [Search Help](#) - [Dissatisfied? Help us improve](#) -  
[Try Google Experimental](#)

---

[Google Home](#) - [Advertising Programs](#) - [Business Solutions](#) - [Privacy](#) - [About Google](#)